# **3 Lever Mortice**

## 2177

### 3 Lever Mortice Deadlock



Application:	<ul> <li>For timber doors hinged on the left or right</li> <li>Keys are suitable for use on doors up to 54mm thick</li> </ul>	
Specification:	<ul> <li>Deadbolt locked/unlocked by key from either side</li> <li>May be keyed alike with 2077, 2157, 2277 and 2477</li> <li>NB: Not suitable for master keying</li> <li>Available with square forend &amp; striking plate</li> <li>Case Size: 65mm (2.5") or 77.5mm (3")</li> <li>Backset: 44.5mm or 57mm</li> <li>Case: Steel, silver powder coat</li> <li>Forend: Stainless steel or brass</li> <li>Striking Plate: Finished to match forend</li> <li>Deadbolt: Brass, with hardened steel rollers</li> <li>Latch Bolt: n/a</li> <li>Follower: n/a</li> <li>Rebate Kit: 2969 (13mm, 19mm or 25mm)</li> <li>Keying Groups: May be supplied to pass, differ and keyed alike. Supplied with 2 steel nickel plated keys</li> <li>Key Blank Number: KB436</li> <li>Keying: 100 standard differs (numbers M101M - M200M)</li> </ul>	Standards: • EN 1634 timber f
Finish:	<ul> <li>SC - Satin Chrome finish</li> <li>PL - Polished Brass finish</li> </ul>	
Fechnical Design:	65mm or 77.5mm E	25.5mm



4-1 assessed for use on 60 minutes fire doors

#### 25.5mm Ô 73mm 120 701 9.5mm 0 Ô 1. $\oplus$ 44.5mm 14.5mm . or 57mm